



OC-001 ORDER FORM

● **High Pressure Oxygen Fill Valve (HPOFV)** For aircraft and other high pressure oxygen systems

Customer: _____ **Date:** ____ / ____ / 20____

Contact Name: _____

Telephone: _____

Delivery Address: _____

● Ordering Code

Include Option(s) from table below:



Custom requirements:

Please specify details for any custom requirements.

PLEASE SEND ORDER TO

FAX: (02) 9780 4210

EMAIL: enquires@oxycheck.com.au

MAIL: 112 Christina Road,
Villawood, NSW 2163

| Feature | Option | Description |
|------------------|-------------|--|
| Inlet Fitting | 1 | 3/8" X 24 UNF -3A thread with 50° female taper, conforms to: AND10089 STYLE E SIZE 3 |
| | C | Custom – Please specify |
| Outlet Fitting | 1 | 3/8" X 24 UNF -3A thread with 50° female taper, conforms to: AND10089 STYLE E SIZE 3 |
| | 2 | 1/2" X 20 UNJF - 3A thread with 37° male taper, conforms to: MS33656 STYLE G SIZE 5 |
| | 3 | 7/16" X 20 UNJF - 3A thread with 37° male taper, conforms to: MS33656 STYLE G SIZE 4 |
| | 4 | 1/2" X 20 UNJF - 3A thread, non-tapered |
| | C | Custom – Please specify |
| Mounting | 1 | 3 X ø 5.1 mm holes in housing flange |
| | C | Custom – Please specify |
| Overall Length | ... | 76 mm (3.0") * |
| Overall Diameter | ... | 45 mm (1.8") * |
| Mass | Check Valve | 182 g (0.4 lb) * |
| | Dust Cap | 23 g (0.05 lb) * |

* Depends on end fittings